

DC ELECTRONIC LOADS

Keithley DC electronic loads are stand-alone, high accuracy instruments for testing and for performance characterization of power conversion devices such as power supplies, battery chargers, solar cells, DC/DC converters, and other power components. Keithley electronic loads offer resolution as low as 0.1mV and 0.01mA to enable detection of subtle changes in power devices. The loads also have high bandwidth dynamic cycling and slew rates as fast as 2.5A/ μ s to thoroughly test the transient performance of power conversion devices.



| 2380 SERIES | |
|-------------------------|---|
| Channels | 1 |
| Maximum power | 200W, 250W, 750W |
| Maximum Voltage/Current | 500V/15A, 120V/60A, 500V/30A |
| Operation Modes | Constant Current (CC), Constant Voltage (CV), Constant Resistance (CR), and Constant Power (CP), Battery Test, LED Simulation |
| Connectivity | GPIB, USB, RS232 |

CHOOSING YOUR DC ELECTRONIC LOAD

DC electronic loads have a wide range of performance to enable testing both static and dynamic performance of power devices. Key capabilities to consider when selecting DC electronic loads are presented below.

1 Output Power, Output Voltage, and Output Current

Ensure that the electronic load can dissipate the output power that your devices can generate. Also make sure that the load is rated for the maximum voltage and maximum current that your devices or components can supply. It is essential that all three parameters are factored in to your selection decision on the dissipation requirements for your DC electronic load.

2 Electronic Load Operating Modes

All electronic loads offer a constant current (CC) operating mode. Most also offer constant voltage (CV) and constant power (CP) operating modes. Some also provide constant resistance (CR) loading. More advanced electronic loads offer battery discharge loading to test battery life characteristics and LED simulation loading to test LED driver modules. Make sure the electronic load you select has the operating modes that you will need.

3 Dynamic Load Testing

If you need to test how your device performs with load changes, ensure that the load you select has a dynamic mode with a transition speed that is fast enough to test the specified transient response of your device. Dynamic modes are typically specified as the range of times that the load will be at each of two current levels. The inverse of twice the shortest time interval determines maximum cycling rate. Shorter time intervals, with fast transitions between loading, stress the power source and provide insight into its stability.

In addition to testing response to fast load changes, it can also be important to determine whether your device can respond at the rate that the load is changing. Ensure electronic load slew rates, often specified in A/ μ s, are high enough to test your device to its slew rate specifications. Ensure these rates are programmable so the electronic load's range of slew rates meets your application needs.

4 Safety Testing

Verifying that your power source does not fail under fault conditions is of critical importance. This is particularly true for a short circuit load condition. Electronic loads can be set for short circuits conditions with the load operating near 0V with milliohm load impedance. Make sure the electronic load you select has short circuit test features.



PRODUCT HIGHLIGHTS

- Multiple operating modes: CV, CC, CR, CP, Battery Test, and LED Simulation
- 0.1 mV/0.01mA V/I readback resolution and 0.025%/0.05% V/I readback accuracy
- Up to 25 kHz dynamic cycling mode with adjustable slew rates up to 2.5A/μs
- Helpful features include voltage rise and fall time measurement, a current monitor output, and list mode load profiles
- Built-in GPIB, USB, RS232 interfaces

2380 Series

Series 2380 programmable DC Electronic Loads are single output, standalone loads with 200W, 250W and 750W models. Multiple operating modes with up to 25 kHz of dynamic cycling, superior voltage/current resolution and readback accuracy together with multiple interface choices make the Series 2380 ideal for testing a power source in your bench.



0.1 mV/0.01mA voltage/current readback resolution give you more confidence in the reading when testing your device.



Dynamic Mode up to 25kHz for faster transient validation of DC power sources.

| MODEL | NUMBER OF OUTPUT | MAXIMUM POWER | MAXIMUM VOLTAGE | MAXIMUM CURRENT | OPERATING MODES | CONNECTIVITY |
|-------------|------------------|---------------|-----------------|-----------------|--|------------------|
| 2380-500-15 | 1 | 200 W | 500 V | 15 A | CV, CC, CR, CP, Battery Test, LED Simulation | GPIB, USB, RS232 |
| 2380-120-60 | 1 | 250 W | 120 V | 60 A | CV, CC, CR, CP, Battery Test, LED Simulation | GPIB, USB, RS232 |
| 2380-500-30 | 1 | 750 W | 500 V | 30 A | CV, CC, CR, CP, Battery Test, LED Simulation | GPIB, USB, RS232 |

RECOMMENDED ACCESSORIES

| | |
|-------------|--|
| 2380-001 | 9-pin Rear Panel Mating Connector |
| 2380-002 | DUT Connection Protective Cover |
| 7007-2 | Double-Shielded Premium IEEE-488 Interface Cable, 2m (6.5 ft) |
| KPCI-488LPA | IEEE-488.2 Interface Board for the PCI Bus |
| USB-B-1 | USB Cable, Type A Connector to Type B Connector, 1m (3.3 ft) |
| 4299-7 | Universal Fixed Rack Mount Kit for 2380-500-15 and 2380-120-60 |
| RMU2U | Fixed Rack Mount Kit for 2380-500-15 and 2380-120-60 |
| 386759800 | RMU2U Rack Mount Cosmetic Filler Panel for 2380-500-15 and 2380-120-60 |
| 2380-RM | Full-Rack-Width Instrument Fixed Rack Mount Kit for 2380-500-30 |

RECOMMENDED SERVICE

| | |
|-----------------|--|
| Model*-1-EW | 3-year factory warranty from date of shipment extended 1 additional year |
| Model*-5Y-EW | 3-year factory warranty from date of shipment extended to 5 years |
| C/Model*-3Y-STD | KeithleyCare 3 YR STD Calibration Plan |
| C/Model*-3Y-DAT | KeithleyCare 3 YR Calibration w/Data Plan |
| C/Model*-5Y-STD | KeithleyCare 5 YR STD Calibration Plan |
| C/Model*-5Y-DAT | KeithleyCare 5 YR Calibration w/Data Plan |

* Replace the specific power supply model number in place of Model Number to generate the appropriate model number for a service item. Example for a 2380-500-15, a 1-year extended warranty model number would be 2380-500-15-EW.

SHIPS WITH PRODUCT

- Quick Start Guide
- User Documentation
- Power Cords
- 9-Pin Rear Mating Connector

LEARN MORE

with the "AC-DC Power Supply Efficiency Testing for Regulatory Standards" Application Note.



ALLICE

Allied Consulting Engineers

make ALLICE your partner

ALLICE MESSTECHNIK GMBH

ALLICE SysTEC GMBH

KELSTERBACHER STRASSE 15-19 60528 FRANKFURT AM MAIN

TEL.: +49(0)69-67724-583 FAX: +49(0)69-67724-582

INFO@ALLICE.DE

www.allice.de

© 2017 ALLICE MESSTECHNIK GMBH & ALLICE SysTEC GMBH- ALLE RECHTE VORBEHALTEN.

© 2017 ALLICE MESSTECHNIK GMBH & ALLICE SysTEC GMBH- ALL RIGHTS RESERVED

VERWENDETE WARENZEICHEN UND SCHUTZRECHTE SIND EIGENTUM DER JEWEILIGEN HERSTELLER.

LOGOS AND COMPANY NAMES LISTED ARE TRADEMARKS OR TRADE NAMES OF THEIR RESPECTIVE OWNERS.