

SWITCH SYSTEMS

Keithley provides a wide array of high integrity switch systems to address the need for switching DC, RF, microwave, and digital I/O signals, whether in matrix, multiplexer, or a combination of configurations. Within our product portfolio you will also find data acquisition systems and digital multimeters with switching options.



	SERIES 3700A*	SYSTEM 46 /46T	707B / 708B
Max Channels / Crosspoints	576 / 2688	32	576 / 96
Card Slots	6	Not applicable	6 / 1
Unique optional card capabilities	High density switching, automatic CJC, long-life switching, FET switching	Not applicable	7072-HV provides 1kV and low current
Interface	GPIB, LAN (LXI), USB-TMC, TSP-Link® Channel Expansion Bus	GPIB	GPIB, LAN (LXI), ACS software, 4200-SCS KTEI software

* Series 3700A Switch Systems are found in this catalog on page 109 under the Data Acquisition product category.

CHOOSING YOUR SWITCH SYSTEMS

The most common selection criteria to help you choose the appropriate switch mainframe for your application.

1 Multiplex Switching

Multiplex switching can be used to connect one instrument to multiple devices (1:N) or multiple instruments to a single device (N:1). Multiplex switching permits multiple simultaneous connections, and sequential or non-sequential switch closures.

2 Matrix Switching

The matrix switch configuration is the most versatile because it can connect multiple inputs to multiple outputs. A matrix is useful when connections must be made between several signal sources and a multi-pin device, such as an integrated circuit or resistor network.

3 Isolated Switch Configurations


The isolated, or independent, switch configuration consists of individual relays, often with multiple poles, with no connections between relays. Isolated relays are not connected to any other circuit, so the addition of external wiring makes them suitable for building very flexible and unique combinations of input/output configurations. Isolated relays are commonly used in power and control applications to open and close different parts of a circuit that are at substantially different voltage levels.




DATA SHEET

PRODUCT HIGHLIGHTS

- Compact RF/microwave switching system only 2U high
- Built-in contact closure counter to monitor switch cycles
- Standard configuration allows up to 32 channels of switching
- Simple control with built-in GPIB/IEEE-488 interface bus
- Channel characterization (S-parameter) data storage



Maximum Configuration: (8) –
Unterminated (S46) or Terminated (S46T) SPDT relays.



Maximum Configuration: (4) –
Unterminated (S46) or Terminated (S46T) multi-pole relays (SP4T, SP6T).

System 46 RF Microwave Switch System

Both terminated and unterminated versions of the Model S46 Switch System are available for testing devices such as cellular and cordless phones, specialized mobile radios, base stations, and RF components, including RFICs. Series 2700 data acquisition systems also offer RF/microwave switch options.

MODEL	MAX. CHANNELS OR CROSSPOINTS PER CHASSIS	FREQUENCY RANGES	RELAYS
S46 (unterminated)	Up to 32 RF/microwave chs	Up to 40GHz	Up to 8 unterminated SPDT coaxial microwave relays and 4 unterminated multi-pole coaxial microwave relays
S46T (terminated)	Up to 32 RF/microwave chs	Up to 40GHz	Up to 8 terminated or unterminated SPDT coaxial microwave relays and 4 terminated or unterminated multi-pole coaxial microwave relays

SHIPS WITH PRODUCT

- Power Cord
- Instruction Manual
- Rack Mount Kit

LEARN MORE

with the “Configuring an Optimal RF/Microwave Switch System” Application Note.





Semiconductor Switch Matrix Mainframes

Models 707B/708B are specifically designed for semiconductor lab and production test environments, delivering ultra low current switching performance using standard triax connectors and cables. For smaller test systems, the Model 708B supports a single 8x12 switch card. For larger systems, the Model 707B can accommodate up to six 8x12 cards.

PRODUCT HIGHLIGHTS

- Remote and manual programming support
- Integrates seamlessly with the Model 4200A-SCS and Series 2600B SourceMeter SMU instruments
- Stores hundreds of switching configurations and channel patterns
- LXI Class C interface supports remote programming and control
- 14 bits of digital I/O



Series 2600B SMUs have an on-board test script processor (TSP) that executes test scripts and controls the switch matrix via the TSPLink.



Models 707B and 708B support a family of matrices designed specifically for low-level semiconductor device testing.

MODEL	MAX. VOLTAGE/CURRENT	MAX. OFFSET CURRENT	REC. FREQUENCY	CONNECTION TYPE
7072	200V / 1A	<1pA	15 MHz	3-lug triax
7072-HV	1300V / 1A	<1pA	4 MHz	3-lug triax
7174A	200V / 2A	<100fA	30 MHz	3-lug triax
7073	200V / 1A	<200pA	30 MHz	BNC

RECOMMENDED ACCESSORIES

CA-126-5A	25-pin Female Digital I/O to 25-pin Male Cable, 3m (10 ft)
2600-TLINK	Digital I/O to Trigger Link Cable, 1m (3.3 ft)
4299-6	Universal Full Rack Mount Kit (for Model 708B)
7007-1	Double-shielded GPIB Cable, 1m (3.3 ft)
7007-2	Double-shielded GPIB Cable, 2m (6.6 ft)
7072	Semiconductor Matrix Card
7072-HV	High Voltage Semiconductor Matrix Card
7072-TRT	Triax Fastening Tool
7079	Slide Rack Mount Kit (for Model 707B)
7173-50	High Frequency, 2-pole, 4x12 Matrix Card
7174A	Low Current Matrix Card

RECOMMENDED SERVICE

R3	3-year Extended Warranty
R5	5-year Extended Warranty
C3	Calibration Service 3 Years
C5	Calibration Service 5 Years
R3DW	Repair Service Coverage 3 Years
R5DW	Repair Service Coverage 5 Years

SHIPS WITH PRODUCT

- User Documentation
- Test Script Builder Software (available at www.tek.com)
- CA-180-4A: CAT 5 Ethernet Crossover Cable, 1m (3.3 ft)
- CA-179-2A: CAT 5 Ethernet Cable, 3m (10 ft)
- CO-7: Line Cord
- Rear Fixed Rack Mount Hardware (707B only)

LEARN MORE

with the “Designing a High Throughput Switch System for Semiconductor Measurements with the Model 707B or 708B Semiconductor Switch Matrix Mainframe” Application Note.



ALLICE

Allied Consulting Engineers

make ALLICE your partner

ALLICE MESSTECHNIK GMBH

ALLICE SysTEC GMBH

KELSTERBACHER STRASSE 15-19 60528 FRANKFURT AM MAIN

TEL.: +49(0)69-67724-583 FAX: +49(0)69-67724-582

INFO@ALLICE.DE

www.allice.de

© 2017 ALLICE MESSTECHNIK GMBH & ALLICE SysTEC GMBH- ALLE RECHTE VORBEHALTEN.

© 2017 ALLICE MESSTECHNIK GMBH & ALLICE SysTEC GMBH- ALL RIGHTS RESERVED

VERWENDETE WARENZEICHEN UND SCHUTZRECHTE SIND EIGENTUM DER JEWEILIGEN HERSTELLER.

LOGOS AND COMPANY NAMES LISTED ARE TRADEMARKS OR TRADE NAMES OF THEIR RESPECTIVE OWNERS.